



*Roto-Prime[®] Self-Priming
Centrifugal Petroleum Pumps*



ROTO-PRIME®

Self-Priming Centrifugal Petroleum Pumps



Roto-Prime® self-priming centrifugal pumps are specifically designed for pumping petroleum products, petrochemicals and solvents. The Roto-Prime design incorporates a variable capacity vane pump which quickly and automatically evacuates air and vapor, making the pump ideal for loading and off-loading transports and stripping hoses.

Roto-Prime® Provides Automatic, Positive Pumping

Roto-Prime® pumps are actually two pumps in one: a variable capacity vane pump used during the priming cycle, and a standard centrifugal pump to move the liquid.

Whenever air or vapor is present at the start of the pumping operation – or when there is a loss of suction because of air or vapor during pumping – the priming pump automatically moves air and vapor from the suction line to discharge line. Once the flowing liquid from the centrifugal portion of the pump builds up sufficient pressure in the discharge system, the pressure backs up through a tube to act on the bottom of the priming pump's movable slide block, placing it in a neutral position during normal operation.



Full Priming

With air or vapor in the lines, pressure of the spring on top of the movable slide holds the priming pump in full pumping position.



Partial Priming

As the pump evacuates air and vapor from the lines, liquid pressure builds up on the underside of this slide, moving it upward toward neutral.




Neutral

When air and vapor are removed, liquid pressure equalizes spring pressure and the pump automatically slides into neutral...where it remains until air and vapor again appear in the system.

GORMAN-RUPP ROTO-PRIME®

The Right Pump For The Job



The GRP33-06 air release valve evacuates air in the suction line to ensure positive self-priming even when pumping against moderate to high static heads. An optional air release valve with stainless steel float is available for use in ethanol service.

1–Suction Inlet

2–Discharge Outlet

3–Balanced Impeller

4–Volute

5–Variable Displacement Priming Pump

6–Mechanical Seal

7–Sealed End Ball Bearings

8–Optional Air Release Valve

Specifications

Pump Size Range: 3" (75 mm) x 2" (50 mm) to 6" (150 mm) x 5" (125 mm)

Max. Capacity: 1450 GPM (91.5 lps)

Max. Head: 390' (118.9 m)

Max. Operating Speed: RS Series (single volute) 1750 rpm, RD Series (double volute) 3450 rpm

Materials of Construction: Aluminum Impeller, Ductile Iron or Cast Steel Housing, Steel or Stainless Steel Shaft, Fluorocarbon Mechanical Shaft Seal*


**Optional seals available to handle a variety of liquid formulations. Consult factory for details.*

Optional Accessories


- Stainless Steel Shafts
- Bronze Impellers
- Companion Flanges
- Swing Check Valves
- Specialized Mechanical Seals
- Air Release Valve
- Available in a variety of motor and base configurations

Pump Performance Data

RS Series



RD Series



FLUID HANDLING EQUIPMENT DESIGNED WITH YOUR NEEDS IN MIND.



★ **Manufacturing Facilities**
● **Distribution Centers**

The Gorman-Rupp Company
Mansfield, Ohio, USA

Mansfield Division
Mansfield, Ohio, USA

Gorman-Rupp International
Mansfield, Ohio, USA

Gorman-Rupp Industries
Bellville, Ohio, USA

Patterson Pump Company
Toccoa, Georgia, USA

**American Machine and
Tool Co., Inc. of Pennsylvania**
Royersford, Pennsylvania, USA

National Pump Company
Fresno, California, USA
Glendale, Arizona, USA (Headquarters)
Lubbock, Texas, USA
Olive Branch, Mississippi, USA
Vienna, Georgia, USA
Zolfo Springs, Florida, USA

★
Gorman-Rupp Africa
Cape Town, South Africa
Durban, South Africa
Johannesburg, South Africa (Headquarters)

Gorman-Rupp Europe
Leeuwarden, Netherlands

Patterson Pump Ireland Limited
County Westmeath, Ireland

Gorman-Rupp of Canada Limited
St. Thomas, Ontario, Canada

Distribution Centers
Bangkok, Thailand
Dubai, United Arab Emirates
Grand Prairie, Texas, USA
Leeuwarden, Netherlands
Sparks, Nevada, USA

Engineering and manufacturing superiority has been a hallmark of Gorman-Rupp since our inception in 1933. Today we bring our products to life in some of the most efficient, modern and state-of-the-art manufacturing facilities in the world. Gorman-Rupp has a selection of nearly 3,000 pump models, and our world-class team of distributors has worked closely with thousands of end users around the world. We have the proven expertise and the resources to specify, manufacture, test and service your pump, and to ensure reliable performance for the long haul.



GRPUMPS.COM



**THE GORMAN-RUPP COMPANY
MANSFIELD DIVISION**
P.O. BOX 1217
MANSFIELD, OHIO 44901-1217 | USA
TEL: 419.755.1011 | FAX: 419.755.1251
GRSALES@GORMANRUPP.COM

GORMAN-RUPP INTERNATIONAL
P.O. BOX 1217
MANSFIELD, OHIO 44901-1217 | USA
TEL: 419.755.1011 | FAX: 419.755.1266
INTSALES@GORMANRUPP.COM

GORMAN-RUPP OF CANADA
70 BURWELL ROAD
ST. THOMAS, ONTARIO N5P 3R7 CANADA
TEL: 519.631.2870 | FAX: 519.631.4624
GRCANADA@GORMANRUPP.COM

