



# The Gorman-Rupp Company

## 7' 6" Below Ground Pump Stations

Gorman-Rupp's 7' 6" (2.3 m) below ground stations, with their inconspicuous low-silhouette entrance tube, are widely used in residential areas. The fiberglass enclosure accommodates two pumps and two motors sized to meet your pumping requirements. The Gorman-Rupp self-priming pump stations require shallower burial than most other pump stations which can save up to 25 feet (7.6 m) of excavation and greatly reduce installation costs. Totally factory-built and pre-tested, the station is delivered to the job site complete, ready to install and operate once simple piping and power connections are made.



### Specifications

|                  |  |
|------------------|--|
| Size:            | 3" (75 mm), 4" (100 mm), 6" (150 mm)   |
| Max Capacity:    | 1,300 GPM (82 lps)                     |
| Max Head:        | 216' (66 m)                            |
| Max Solids:      | 3" (76 mm)                             |
| Max Temperature: | 160 F (71 C)                           |
| Motor - Voltage: | 200 V 3P, 230 V 1P, 230 V 3P, 460 V 3P |
| Motor - Cycles:  | 60 Hz                                  |
| Horsepower:      | 2 HP - 50 HP                           |

### Features

#### Single Source Responsibility

---

Gorman-Rupp designs, engineers and manufactures the entire pumping system to ensure that the system meets your requirements and performs reliably year after year. If there is a problem with the system you only have to make one call. Gorman-Rupp is responsible for the entire system, from pumps and controls to the lights and fans in our enclosures.

#### Super T Series Pumps

---



Gorman-Rupp self-priming centrifugal solids-handling Super T Series pumps are specifically designed for sewage and industrial wastewater handling applications. The heavy-duty construction and easy-to-service design have made Gorman-Rupp T Series pumps the standard of the industry.

#### Controls

---

The Gorman-Rupp team of electrical, mechanical and hydraulic engineers work closely throughout the development of each pumping system to ensure that the entire hydro-electrical system works in harmony to meet your system requirements – accurately and reliably. All Gorman-Rupp controls are manufactured of the highest quality components and are available U.L. and C.S.A. listed (not standard).

*Specifications are subject to change. Please contact your Gorman-Rupp Distributor for more details.*



**The Gorman-Rupp  
Company  
Mansfield Division**  
P.O. Box 1217  
Mansfield, Ohio 44901-1217,  
USA  
Tel: 419-755-1011  
Fax: 419-755-1251  
E-mail:  
grsales@gormanrupp.com

**The Gorman-Rupp International  
Company**  
P.O. Box 1217  
Mansfield, Ohio 44901-1217, USA  
Tel: 419-755-1011  
Fax: 419-755-1266  
E-mail: intsales@gormanrupp.com

**Gorman-Rupp of Canada, Ltd.**  
70 Burwell Road  
St. Thomas, Ontario N5P 3R7,  
Canada  
Tel: 519-631-2870  
Fax: 519-631-4624  
E-mail:  
grcanada@grcanada.com



**[GRpumps.com](http://GRpumps.com)**

©1998-2008 The Gorman-Rupp Company. All Rights Reserved.