



The Gorman-Rupp Company

7' x 10' Above Ground Pressure Booster Stations

Gorman-Rupp's 7' x 10' (2.1 m x 3.1 m) Above Ground Pressure Booster Station is a complete system, ready for immediate installation and hookup to power and piping. The low silhouette and color of the Quonset-type fiberglass enclosure blends in with surrounding landscaping. The fiberglass enclosure resists corrosion, mildew, fungus and mold. Two-way sliding cover provides easy access to all equipment for maintenance or service. Vandal resistant door hardware and lockable sliding cover are standard for added security.



Specifications

Size:	2" (50 mm), 3" (75 mm), 4" (100 mm), 5" (125 mm), 6" (150 mm)
Max Capacity:	1,300 GPM (82 lps)
Max Temperature:	160 F (71 C)
Motor - Voltage:	200 V 3P, 230 V 1P, 230 V 3P, 460 V 3P
Motor - Cycles:	60 Hz

Features

Controls

Dependable Station Controllers engineered to meet your requirements have a variety of adjustable pressure controls, H-O-A selectors for each pump, overload reset buttons and circuit breakers for station accessories. Automatic controls operate pump functions and warning systems. All field connections are clearly identified for fast and efficient electrical hookup.

Pumps

Booster Pumps used in our packaged stations are designed for long lasting and trouble-free use. Whether your engineered system requires vertical in-line, end suction, split case or vertical turbine pumps, you can depend on our durable design.

Specifications are subject to change. Please contact your Gorman-Rupp Distributor for more details.



The Gorman-Rupp Company
Mansfield Division
P.O. Box 1217
Mansfield, Ohio 44901-1217,
USA
Tel: 419-755-1011
Fax: 419-755-1251
E-mail:
grsales@gormanrupp.com

The Gorman-Rupp International Company
P.O. Box 1217
Mansfield, Ohio 44901-1217, USA
Tel: 419-755-1011
Fax: 419-755-1266
E-mail: intsales@gormanrupp.com

Gorman-Rupp of Canada, Ltd.
70 Burwell Road
St. Thomas, Ontario N5P 3R7,
Canada
Tel: 519-631-2870
Fax: 519-631-4624
E-mail:
grcanada@grcanada.com



