



# The Gorman-Rupp Company

## GMS Series (G Series)

The GMS Series is designed for intermittent or medium duty service for applications in the operating ranges noted. These units are available with head and backhead jackets for temperature control, carbon graphite bushings for low viscosity liquids, silicon carbide bushings for wear resistance. For continuous duty service, or for handling viscous liquids, see heavy duty GHC pumps.



### Specifications

Size:	1" (25 mm), 1-1/2" (37.5 mm), 2" (50 mm), 2-1/2" (62.5 mm), 3" (75 mm), 4" (100 mm), 5" (125 mm), 6" (150 mm)
Max Capacity:	600 GPM (38 lps)
Max Viscosity:	250,000 SSU (54,000 cST)
Max Pressure:	150 PSI (11 BAR)
Min Temperature:	-60 F (-51 C)
Max Temperature:	450 F (232 C)
Materials of Construction:	Cast Iron

*Specifications are subject to change. Please contact your Gorman-Rupp Distributor for more details.*



**The Gorman-Rupp Company**  
**Mansfield Division**  
P.O. Box 1217  
Mansfield, Ohio 44901-1217,  
USA  
Tel: 419-755-1011  
Fax: 419-755-1251  
E-mail:  
grsales@gormanrupp.com

**The Gorman-Rupp International Company**  
P.O. Box 1217  
Mansfield, Ohio 44901-1217, USA  
Tel: 419-755-1011  
Fax: 419-755-1266  
E-mail: intsales@gormanrupp.com

**Gorman-Rupp of Canada, Ltd.**  
70 Burwell Road  
St. Thomas, Ontario N5P 3R7,  
Canada  
Tel: 519-631-2870  
Fax: 519-631-4624  
E-mail:  
grcanada@grcanada.com



[GRpumps.com](http://GRpumps.com)

©1998-2009 The Gorman-Rupp Company. All Rights Reserved.