



10' Below Ground Lift Stations

Gorman-Rupp's years of experience working with design engineers led to the performance and control features that have been incorporated into the 10' (3.1 m) diameter below ground pump lift station. This pre-engineered unit offers an extensive selection of pumps, motors, controls, piping and accessories. The fiberglass enclosure accommodates 3", 4" or 6" (75 mm, 100 mm, or 150 mm) pumps in duplex or triplex configuration, or 8" or 10" (150 mm or 250 mm) pumps in duplex configuration. Units are delivered right to the job site, ready for lowering into position over wet well. All you do is hook up simple piping and power connections. The only thing visible above ground is the inconspicuous 44" (1.1 m) diameter entrance tube.



Specifications

Size:	3" (75 mm), 4" (100 mm), 6" (150 mm), 8" (200 mm), 10" (250 mm)
Max Capacity:	3,200 GPM (202 lps)
Max Solids:	3" (76 mm)
Max Temperature:	160 F (71 C)
Motor - Voltage:	200 V 3P, 230 V 1P, 230 V 3P, 460 V 3P
Motor - Cycles:	60 Hz
Horsepower:	2 HP - 75 HP

Features

Single Source Responsibility

Gorman-Rupp designs, engineers and manufactures the entire pumping system to ensure that the system meets your requirements and performs reliably year after year. If there is a problem with the system you only have to make one call. Gorman-Rupp is responsible for the entire system, from pumps and controls to the lights and fans in our enclosures.

Super T Series Pumps

Gorman-Rupp self-priming centrifugal solids-handling Super T Series pumps are specifically designed for sewage and industrial wastewater handling applications. The heavy-duty construction and easy-to-service design have made Gorman-Rupp T Series pumps the standard of the industry.

Controls

The Gorman-Rupp team of electrical, mechanical and hydraulic engineers work closely throughout the development of each pumping system to ensure that the entire hydro-electrical system works in harmony to meet your system requirements – accurately and reliably. All Gorman-Rupp controls are manufactured of the highest quality components and are available U.L. and C.S.A. listed (not standard).



**The Gorman-Rupp
Company
Mansfield Division**
P.O. Box 1217
Mansfield, Ohio 44901-1217,
USA
Tel: 419-755-1011
Fax: 419-755-1251
E-mail:
grsales@gormanrupp.com

**The Gorman-Rupp International
Company**
P.O. Box 1217
Mansfield, Ohio 44901-1217, USA
Tel: 419-755-1011
Fax: 419-755-1266
E-mail: intsales@gormanrupp.com

Gorman-Rupp of Canada, Ltd.
70 Burwell Road
St. Thomas, Ontario N5P 3R7,
Canada
Tel: 519-631-2870
Fax: 519-631-4624
E-mail:
grcanada@grcanada.com



GRpumps.com

©1998-2010 The Gorman-Rupp Company. All Rights Reserved.