

Gorman-Rupp 60 Series pumps are standard centrifugal, high pressure, high volume pumps with exceptional efficiencies (up to 85%). Discharge on many models can be placed in any position by turning the pump casing.



Specifications

Size:	2" (50 mm), 2-1/2" (62.5 mm), 3" (75 mm), 4" (100 mm), 5" (125 mm), 6" (150 mm), 8" (200 mm), 10" (250 mm), 12" (300 mm)
Max Capacity:	6,800 GPM (429 lps)
Max Head:	500' (152 m)
Max Solids:	3" (76 mm)
Max Temperature:	160 F (71 C)
Materials of Construction:	Cast Iron, Cast Steel, Ductile Iron

Specifications are subject to change. Please contact your Gorman-Rupp Distributor for more details.



The Gorman-Rupp Company
Mansfield Division
 P.O. Box 1217
 Mansfield, Ohio 44901-1217,
 USA
 Tel: 419-755-1011
 Fax: 419-755-1251
 E-mail:
 grsales@gormanrupp.com

The Gorman-Rupp International Company
 P.O. Box 1217
 Mansfield, Ohio 44901-1217, USA
 Tel: 419-755-1011
 Fax: 419-755-1266
 E-mail: intsales@gormanrupp.com

Gorman-Rupp of Canada, Ltd.
 70 Burwell Road
 St. Thomas, Ontario N5P 3R7,
 Canada
 Tel: 519-631-2870
 Fax: 519-631-4624
 E-mail:
 grcanada@grcanada.com



GRpumps.com

©1998-2010 The Gorman-Rupp Company. All Rights Reserved.