

# **Standard Centrifugal Pump**

# Model VG4D3-B

Size 5" x 4"

#### **PUMP SPECIFICATIONS**

Size: 5" x 4" (127 mm x 102 mm) Flanged.

Casing: Gray Iron 40.

Maximum Operating Pressure 181 psi (1248 kPa).\*

Enclosed Type, Six Vane Impeller: Gray Iron 40.

Handles 5/8" (15,9 mm) Diameter Spherical Solids.

Impeller Shaft: Steel 1045.

Shaft Sleeve: Stainless Steel 420.

Seal Plate: Gray Iron 40.

**Bearing Housing:** Gray Iron 40. **Radial Bearing:** Open Single Row Ball.

Thrust Bearing: Open Double Row Ball.

Bearing Lubrication: SAE 30 Non-Detergent Oil.

Gaskets: Nitrile Rubber.


O-Ring: Fluorocarbon (DuPont Viton® or Equivalent).

Hardware: Standard Plated Steel.


Oil Level Sight Gauge.

Optional Equipment: NPT Suction and Discharge Flanges. Strainer. Stainless Steel Impeller. Mechanical Seal with Fluorocarbon Elastomers (DuPont Viton® or Equivalent). Manual Discharge Check Valve.

\*Consult Factory for Applications Exceeding Maximum Pressure and/or Temperature Indicated.







#### **SEAL DETAIL**

Type 1, Mechanical, Self-Lubricated. Carbon Rotating Face. Ceramic Stationary Seat. Buna-N Elastomers. Stainless Steel Cage and Spring. Maximum Temperature of Liquid Pumped, 160°F (71°C).\*



## **GORMAN-RUPP PUMPS**

www.grpumps.com

Specifications Subject to Change Without Notice


Printed in U.S.A.


#### Specification Data

**SECTION 70, PAGE 820** 

APPROXIMATE DIMENSIONS and WEIGHTS

NET WEIGHT: SHIPPING WEIGHT: EXPORT CRATE SIZE: 508 LBS. (230,4 KG.) 550 LBS. (257,6 KG.) 13 CU. FT. (0,37 CU. M.)





PERFORMANCE BASED ON WATER



### **GORMAN-RUPP PUMPS**

www.grpumps.com

Specifications Subject to Change Without Notice

Printed in U.S.A.


**Curve Data** 

WATER


Sec. 70

**PAGE 820.1** 

**AUGUST 2023** 



**PERFORMANCE BASED ON WATER** 





#### GORMAN-RUPP PUMPS

www.grpumps.com

Specifications Subject to Change Without Notice

Printed in U.S.A.

**Curve Data** 


**BASED ON** 

**WATER** 


Sec. 70

**PAGE 820.2** 

**AUGUST 2023** 



**50 HERTZ PERFORMANCE BASED ON WATER** 





#### **GORMAN-RUPP PUMPS**

www.grpumps.com

Specifications Subject to Change Without Notice

Printed in U.S.A