Basic Pedestal

Sec. 70

PAGE 1451





Standard Centrifugal Pump

Model VGH6E31-B

Size 8" x 6"

PUMP SPECIFICATIONS

Size: 8" x 6" (203 mm x 152 mm) Raised Face Flanges.

Casing: Ductile Iron.

Maximum Casing Pressure 263 psi (1813 kPa).* Maximum Operating Pressure 250 psi (1723 kPa) at Temperatures up to 100°F (37°C) Based on System Component Limitations.

Enclosed Type, Six Vane Impeller: Gray Iron 40. Handles1" (25,4 mm) Diameter Spherical Solids.

Impeller Shaft: Steel 1045.

Two Replaceable Wear Rings: Gray Iron 25.

Seal Plate: Ductile Iron. **Bypass Flush Piping.**

Bearing Housing: Gray Iron 25.

Radial Bearing: Open Cylindrical Roller. Thrust Bearing: Open Double Row Ball.

Bearing Lubrication: SAE 30 Non-Detergent Oil.


Gaskets: Nitrile Rubber.


Hardware: Standard Plated Steel. **Bearing Housing Level Oiler.**

Optional Equipment: Strainer. NPT Suction and Discharge Flanges. Discharge Check Valve. Stainless Steel Impeller.

Consult Factory for Optional Seals.







SEAL DETAIL

Mechanical, Self-Lubricated. Silicon Carbide Faces. Rotating and Stationary Fluorocarbon Elastomers (DuPont Viton® or Equivalent). Stainless Steel 316 Shaft Sleeve and Spring. Maximum Temperature of Liquid Pumped, 160°F (71°C).*



GORMAN-RUPP PUMPS


www.grpumps.com

Specifications Subject to Change Without Notice

Specification Data


SECTION 70, PAGE 1451

APPROXIMATE DIMENSIONS and WEIGHTS **NET WEIGHT:** 749 LBS. (340 KG.) SHIPPING WEIGHT: 801 LBS. (363 KG.) EXPORT CRATE SIZE: 27.1 CU. FT. (0,77 CU. M.)





WATER





GORMAN-RUPP PUMPS

www.grpumps.com


Specifications Subject to Change Without Notice

Curve Data


Sec. 70


PAGE 1451.1

JANUARY 2016



60 HERTZ PERFORMANCE BASED ON WATER





60 HERTZ PERFORMANCE BASED ON WATER



GORMAN-RUPP PUMPS

www.grpumps.com

Specifications Subject to Change Without Notice


Curve Data

Sec. 70

PAGE 1451.2


JANUARY 2016

C-1-02



60 HERTZ PERFORMANCE BASED ON PETROLEUM

WATER





GORMAN-RUPP PUMPS

www.grpumps.com

Specifications Subject to Change Without Notice

Curve Data


Sec. 70

PAGE 1451.3

10

C-3-03-R

JANUARY 2016



9

7

ਠੁ


50 HERTZ PERFORMANCE BASED ON WATER

10-

O O O OF

LITRES 6 '

WARE 19.69" DIA.



50 HERTZ PERFORMANCE BASED ON PETROLEUM



GORMAN-RUPP PUMPS

www.grpumps.com

Specifications Subject to Change Without Notice