



## Basic Pedestal Standard Centrifugal Pump Model 68A2-B

### Size 8" x 8"

#### PUMP SPECIFICATIONS

**Size:** 8" (203 mm) Female NPT Suction.  
8" (203 mm) Flanged Discharge.

**Casing:** Gray Iron 30.

Maximum Operating Pressure 92 psi (634 kPa).\*

**Open Type, Six Vane Impeller:** Gray Iron 30.

Handles 1 1/8" (28,6 mm) Diameter Spherical Solids.

**Impeller Shaft:** Alloy Steel 4150.

**Replaceable Wear Ring:** Copper Alloy C83600.

**Pedestal:** Gray Iron 30.

**Seal Liner:** Copper Alloy C26000.

**Radial Bearing:** Open Single Row Ball.

**Thrust Bearing:** Open Double Row Ball.

**Bearing Lubrication:** SAE 30 Non-Detergent Oil.

**Suction Head:** Gray Iron 30.

**Gaskets:** Vegetable Fiber.



**Hardware:** Standard Plated Steel.

**Strainer.**

**Oil Level Sight Gauge.**

**Optional Equipment:** 8" NPT Discharge Flange. Discharge Check Valve. Hand Primer.

*\*Consult Factory for Applications Exceeding Maximum Pressure and/or Temperature Indicated.*



#### SEAL DETAIL

Double, Grease Lubricated with Spring-Loaded Grease Cup. Sintered Bronze Stationary Seal Seats. Steel Rotating Faces. Neoprene Packing Rings. Maximum Temperature of Liquid Pumped, 110°F (43°C). Maximum Suction Pressure 10 psi (69 kPa).\*



## GORMAN-RUPP PUMPS

www.grpumps.com

Specifications Subject to Change Without Notice



Printed in U.S.A.

# Specification Data

APPROXIMATE DIMENSIONS and WEIGHTS

NET WEIGHT: 460 LBS. (208,7 KG.)  
 SHIPPING WEIGHT: 483 LBS. (219,1 KG.)  
 EXPORT CRATE: 27.6 CU. FT. (0,78 CU. M.)

SECTION 70, PAGE 1500




GORMAN-RUPP PUMPS

www.grpumps.com

Specifications Subject to Change Without Notice

Printed in U.S.A.

PERFORMANCE  
BASED ON  
WATER



GORMAN-RUPP PUMPS

www.grpumps.com

Specifications Subject to Change Without Notice

Printed in U.S.A.