PAGE 1501 JANUARY 2012

ABCDE

Basic Pedestal



Self Priming Centrifugal Pump Models 83B3-B, 83B31-B and 83B52-B

Size 3" x 3"

PUMP SPECIFICATIONS

Size: 3" x 3" (76 mm x 76 mm) NPT - Female.

Casing (Models 83B3-B and 83B52-B): Gray Iron 30.

(Model 83B31-B): Ductile Iron 65-45-12.

Maximum Operating Pressure 117 psi (807 kPa)*. Semi-Open Type, Four Vane Impeller: Gray Iron 30. Handles 13/16" (20,6 mm) Diameter Spherical Solids

Impeller Shaft: Carbon Steel 1045/1046. Replaceable Wear Plate: Carbon Steel 1026.

Pedestal: Gray Iron 30. Shaft Sleeve: Alloy Steel 4130.

Seal Plate (Models 83B3-B and 83B52-B): Gray Iron 30.

(Model 83B31-B): Ductile Iron 65-45-12.

Flap Valve: Buna-N W/Nylon Reinforcement and Gray Iron 30.


Radial and Thrust Bearings: Open Single Row Ball.
Bearing Lubrication: SAE 30 Non-Detergent Oil.

Suction Flange: Gray Iron 25. Gaskets: Cork and Vegetable Fiber. Hardware: Standard Plated Steel. Discharge Service Tee: Gray Iron 30.

Oil Level Sight Gauge.

Optional Equipment: Consult Factory.

*Consult Factory for Applications Exceeding Maximum Pressure and/or Temperature Indicated.




83B3-B and 83B31-B SEAL DETAIL Type 2, Mechanical, Self-Lubricated.

Carbon Rotating Face. Ni-Resist Fluorocarbon Stationary Face. (DuPont Viton® Elastomers Stainless Steel 18-8 Equivalent). Cage and Spring. Maximum Temperature of Liquid Pumped, 160°F (71 °C).*

83B52-B SEAL DETAIL

Mechanical. Type 31, Self-Lubricated. Silicon Carbide Rotating and Stationary Faces. Fluorocarbon Elastomers (DuPont Viton® or Equivalent). Stainless Steel 18-8 Cage and Spring. Maximum Temperature of Liquid Pumped 160°F (71°C).*



83B3-B SHOWN

FLAP VALVE

IMPELLER



SUCTION FLANGE

THE GORMAN-RUPP COMPANY ● MANSFIELD. OHIO

GORMAN-RUPP OF CANADA LIMITED ● ST. THOMAS, ONTARIO, CANADA

PEDESTAL

SEAL ASSEMBLY SHAFT

IMPELLER

www.grpumps.com

Specifications Subject to Change Without Notice

Printed in U.S.A.





Specification Data

SECTION 50, PAGE 1501

APPROXIMATE DIMENSIONS and WEIGHTS

NET WEIGHT: 136 LBS. (61,7 KG.) SHIPPING WEIGHT: 150 LBS. (68,0 KG.) EXPORT CRATE: 8.5 CU. FT. (0,24 CU. M.)







THE GORMAN-RUPP COMPANY ● MANSFIELD, OHIO

GORMAN-RUPP OF CANADA LIMITED ● ST. THOMAS, ONTARIO, CANADA

Specifications Subject to Change Without Notice

Printed in U.S.A.


Sec. 50

PAGE 1501.1 **JANUARY 2012**


T-7-94-R

ABCDE

BASED ON PETROLEUM



50 HERTZ PERFORMANCE BASED ON WATER





THE GORMAN-RUPP COMPANY ● MANSFIELD. OHIO

GORMAN-RUPP OF CANADA LIMITED ● ST. THOMAS, ONTARIO, CANADA

Specifications Subject to Change Without Notice

Printed in U.S.A.