#### **Basic Pedestal**



# Standard Centrifugal Pump Model VG1 1/2C3-B

Size 2 1/2" x 1 1/2"

#### **PUMP SPECIFICATIONS**

Size: 2 1/2" x 1 1/2" (64 mm x 38 mm) Flanged.

Casing: Gray Iron 40.

Maximum Operating Pressure 182 psi (1255 kPa).\* Enclosed Type, Six Vane Impeller: Gray Iron 40. Handles 5/16" (7,9 mm) Diameter Spherical Solids.

Impeller Shaft: Steel 1045.

**Shaft Sleeve:** Stainless Steel 420.

Seal Plate: Gray Iron 40.

Bearing Housing: Gray Iron 40.

Radial Bearing: Open Single Row Ball.

Thrust Bearing: Open Double Row Ball.

Bearing Lubrication: SAE 30 Non-Detergent Oil.

Gaskets: Nitrile Rubber.


O-Ring: Fluorocarbon (DuPont Viton® or Equivalent).

Hardware: Standard Plated Steel.


Oil Level Sight Gauge.

Optional Equipment: NPT Suction and Discharge Flanges. Strainer. Stainless Steel Impeller. Mechanical Seal with Fluorocarbon Elastomers (DuPont Viton® or Equivalent).

\*Consult Factory for Applications Exceeding Maximum Pressure and/or Temperature Indicated.







#### **SEAL DETAIL**

Type 1, Mechanical, Self-Lubricated. Carbon Rotating Face. Ceramic Stationary Seat. Buna-N Elastomers. Stainless Steel and/or Brass Cage and Spring. Maximum Temperature of Liquid Pumped, 160°F (71°C).\*



# **GORMAN-RUPP PUMPS**

www.grpumps.com

Specifications Subject to Change Without Notice


Printed in U.S.A.


## **Specification Data**

**SECTION 70, PAGE 150** 

APPROXIMATE DIMENSIONS and WEIGHTS

NET WEIGHT: 82 LBS. (37,2 KG.) SHIPPING WEIGHT: 92 LBS. (41,7 KG.) EXPORT CRATE SIZE: 5.6 CU. FT. (0,16 CU. M.)





PERFORMANCE BASED ON WATER



## **GORMAN-RUPP PUMPS**

www.grpumps.com


Specifications Subject to Change Without Notice

Printed in U.S.A.


**Curve Data** 


Sec. 70

**PAGE 150.1 JANUARY 2016** 



**PERFORMANCE BASED ON WATER** 





**PERFORMANCE BASED ON WATER** 



LITRES PER SECOND CUBIC METRES O

# **GORMAN-RUPP PUMPS**

5

00 65 5.

25

10-15-

'n

www.grpumps.com

Specifications Subject to Change Without Notice

Printed in U.S.A.


© 1-5-01-R

Sec. 70


PAGE 150.2 JANUARY 2016



WATER



PERFORMANCE BASED ON WATER





#### **GORMAN-RUPP PUMPS**

www.grpumps.com

Specifications Subject to Change Without Notice

Printed in U.S.A.