



Electric Motor Driven, Stainless Steel Submersible Pump Model S4D65-E10 Size 4"

PUMP SPECIFICATIONS**Diffuser:** Stainless Steel CD4MCu;

Maximum Operating Pressure 108 psi (747 kPa).*

Impeller: Stainless Steel CD4MCu.**Wear Plate:** Stainless Steel CD4MCu.**Seal Plate:** Stainless Steel CD4MCu.**Intermediate:** Stainless Steel 316.**Casing:** Stainless Steel 316.**Motor Housing:** Stainless Steel 316.**Motor Shaft:** Stainless Steel 316.**Shaft Sleeve:** Stainless Steel 316.**Bearings:** Upper - Open Single Row Ball Bearing.

Lower - Two Synthetic Seals, Double Row Ball Bearing.

Discharge Flange: Stainless Steel 316.**Gaskets:** Buna-N with Compressed Synthetic Fiber.**O-Rings:** Fluorocarbon (DuPont Viton® or Equivalent).**Wetted Hardware:** Stainless Steel 316.**Strainer:** Stainless Steel 316; 50.6% Open Area,
0.375" (9.5 mm) Diameter Openings.**Hoisting Bail:** Stainless Steel 316.**Standard Equipment****NEMA Type 3R Rainproof Control Box.** *(See Section 130, Page 90.)*

Provides On-Off, Circuit Breaker and Motor Overload Protection.

Optional Equipment**Liquid Level Control** *(See Sec. 130, Page 150.)*



a. Turtle Type Pressure Activated Level Switch.

b. Float Activated Level Switch.

Staging Adapter Kit.**MOTOR/CABLE SPECIFICATIONS****Motor:** Oil Filled Enclosure; 10.0 H.P.; 3450 R.P.M.; Three Phase: 460/575
Volt, 60 Hz, 17/13.6 Full Load AMPS, 12.2 kW (Max.)**Power Cable:** CPE/CSPE Jacket, Type GGC; 6 Wire; 8 AWG.

3 Power Conductors, 2 Ground Conductor and 1 Ground Check.

Nominal Length 50 Feet (15 m.) Standard.

*(Specify Alternate Length at Time of Order.)***Recommended Generator Size:** 15 kW Across the Line Start.* Consult Factory for Applications Exceeding Maximum
Pressure and/or Temperature Indicated.**SEAL DETAIL**

Tandem, Oil Lubricated.

Upper Seal: Type 21, Mechanical. Carbon Rotating
Face. Ceramic Stationary Faces. Fluorocarbon
Elastomers. Stainless Steel 18-8 Cage and Spring.**Lower Seal:** Type 2, Mechanical. Silicon Carbide
Rotating and Stationary Faces. Fluorocarbon
Elastomers (DuPont Viton® or Equivalent). Stainless
Steel 303/304 Cage and Spring. Maximum
Temperature of Liquid Pumped, 122°F (50°C).***GORMAN-RUPP PUMPS**

www.grpumps.com

Specifications Subject to Change Without Notice



Printed in U.S.A.

Specification Data

SECTION 130, PAGE 940

APPROXIMATE
DIMENSIONS and WEIGHTS

NET WEIGHT: 361 LBS. (163,7 KG.)
SHIPPING WEIGHT: 381 LBS. (172,8 KG.)
EXPORT CRATE: 11.3 CU. FT. (0,32 CU. M.)



GORMAN-RUPP PUMPS

www.grpumps.com

Specifications Subject to Change Without Notice

Printed in U.S.A.